

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name/designation**

320 Syntic-Total - PUR adhesive  
UFI: 7GV0-40N2-K00U-H5WE

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Adhesives, sealants

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

Renia Gesellschaft mbH  
Ostmerheimer Straße 516 Telephone: +492216307990  
51109 Köln E-mail: info@renia.com  
Deutschland Website: www.renia.com

**Department responsible for information**

E-mail (competent person) labor@renia.com

**1.4 Emergency telephone number**

24 hr. emergency phone number: +49-221-630799-17

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

- \* Flam. Liq. 2; flammable liquids; H225 Highly flammable liquid and vapour.
- \* Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation.
- \* STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



GHS02 GHS07

**Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**\* Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.  
P280 Wear protective gloves and eye/face protection.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

- \* acetone; propan-2-one; propanone

**Supplemental hazard information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

**SECTION 3: Composition/information on ingredients.**

**3.2 Mixtures**

**Description**

Polyurethane-Prepolymers with stabilizers in a mixture of organic solvents

**Hazardous ingredients**

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
* 67-64-1 200-662-2 606-001-00-8	<b>acetone; propan-2-one; propanone</b> 01-2119471330-49 Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 ATE (oral): = 5.800 mg/kg ATE (dermal): > 15.800 mg/kg ATE (inhalative): = 76 ppmV (4 h)	35,0 < 50,0
* 141-78-6 205-500-4 607-022-00-5	<b>ethyl acetate</b> 01-2119475103-46 Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 ATE (oral): > 5.620 mg/kg ATE (dermal): > 18.000 mg/kg ATE (inhalative): = 56 mg/L (4 h)	25,0 < 35,0
* 1330-20-7 215-535-7 601-022-00-9	<b>xylene</b> 01-2119488216-32 Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 / STOT SE 3 H335 / STOT RE 2 H373 ATE (oral): = 3.523 mg/kg ATE (dermal): = 12.126 mg/kg ATE (inhalative): = 27.571 mg/m <sup>3</sup> (4 h)	5,0 < 10,0

**Remark**

Full text of H- and EUH-statements: see section 16. Full text of H-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

Remove affected person from the danger area and lay down.

**Following inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

**Following skin contact**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

**After eye contact**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

\* **Following ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

dizziness. Nausea.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Transport affected person in lying position, in case of shortness of breath in half-sitting position. Where appropriate artificial ventilation.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Extinguishing powder, ABC-powder, spray mist, (water), Dry sand.

**Unsuitable extinguishing media**

Full water jet. Strong water jet.

**5.2 Special hazards arising from the substance or mixture**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

Flammable. Vapours can form explosive mixtures with air. Do not inhale explosion and combustion gases. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

**5.3 Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**5.4 Additional information**

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with eyes and skin. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray.

**6.2 Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains.

**6.3 Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

**Advices on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advices on general occupational hygiene**

When using do not eat, drink, smoke, sniff. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

**Further information**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours/aerosols must be exhausted directly at the point of origin. Take precautionary measures against static discharges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Ensure adequate ventilation of the storage area.

**Hints on joint storage**

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances. Store packaging and ignitable materials separately. Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Floors should be impervious, resistant to liquids and easy to clean. Store small packages in a suitable, robust cabinet.

**7.3 Specific end use(s)**

Adhesives, sealants, Roller application or brushing of adhesive and other coating.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

	CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
*	67-64-1	acetone; propan-2-one; propanone	WEL	1.210 / 3.620 ( - ) mg/m <sup>3</sup>
*	141-78-6	ethyl acetate	WEL	734 / 1.468 ( - ) mg/m <sup>3</sup>
*	1330-20-7	xylene	WEL	220 / 441 ( - ) mg/m <sup>3</sup>

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

**Additional information**

Long-term: Long-term occupational exposure limit value  
 short-term: short-term occupational exposure limit value

**Biological limit values**

CAS No.	Substance name	Source	Value/ Test material
* 1330-20-7	xylene	BMGV	650 mmol/mol creatinine / urine

**DNEL worker**

CAS No.	Substance name	DNEL type	DNEL value
* 67-64-1	acetone; propan-2-one; propanone	DNEL acute inhalative (systemic)	2.420 mg/L
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term inhalative (systemic)	1.210 mg/L
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term dermal (systemic)	186 mg/kg
* 141-78-6	ethyl acetate	DNEL long-term inhalative (systemic)	1,468 mg/L
* 141-78-6	ethyl acetate	DNEL acute inhalative (local)	1,468 mg/L
* 141-78-6	ethyl acetate	DNEL long-term dermal (systemic)	63 mg/kg
* 1330-20-7	xylene	DNEL long-term inhalative (systemic)	77 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL acute inhalative (systemic)	289 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL acute inhalative (local)	289 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL long-term dermal (systemic)	180 mg/kg bw/day

**DNEL Consumer**

CAS No.	Substance name	DNEL type	DNEL value
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term dermal (systemic)	62 mg/kg
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term inhalative (systemic)	200 mg/L
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term oral (repeated)	62 mg/kg
* 141-78-6	ethyl acetate	DNEL acute inhalative (systemic)	0,734 mg/L
* 141-78-6	ethyl acetate	DNEL long-term inhalative (local)	0,734 mg/L
* 141-78-6	ethyl acetate	DNEL long-term dermal (systemic)	37 mg/kg
* 141-78-6	ethyl acetate	DNEL long-term inhalative (systemic)	0,037 mg/L
* 141-78-6	ethyl acetate	DNEL long-term oral (repeated)	4,5 mg/kg
* 141-78-6	ethyl acetate	DNEL acute inhalative (local)	0,367 mg/L
* 1330-20-7	xylene	DNEL long-term inhalative (systemic)	14,8 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL long-term dermal (systemic)	108 mg/kg bw/day
* 1330-20-7	xylene	DNEL long-term oral (repeated)	1,6 mg/kg bw/day

**PNEC**

CAS No.	Substance name	PNEC type	PNEC Value
* 67-64-1	acetone; propan-2-one; propanone	PNEC aquatic, freshwater	10,6 mg/L
* 67-64-1	acetone; propan-2-one; propanone	PNEC aquatic, marine water	1,06 mg/L
* 67-64-1	acetone; propan-2-one; propanone	PNEC sediment, freshwater	30,4 mg/L
* 67-64-1	acetone; propan-2-one; propanone	PNEC sediment, marine water	3,04 mg/L
* 67-64-1	acetone; propan-2-one; propanone	PNEC soil, marine water	29,5 mg/L
* 141-78-6	ethyl acetate	PNEC aquatic, freshwater	0,26 mg/L

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

*	141-78-6	ethyl acetate	PNEC aquatic, marine water	0,026 mg/L
*	141-78-6	ethyl acetate	PNEC sediment, freshwater	0,34 mg/kg
*	141-78-6	ethyl acetate	PNEC sediment, marine water	0,034 mg/kg
*	141-78-6	ethyl acetate	PNEC soil, freshwater	0,22 mg/kg
*	1330-20-7	xylene	PNEC aquatic, freshwater	0,327 mg/L
*	1330-20-7	xylene	PNEC aquatic, marine water	0,327 mg/L
*	1330-20-7	xylene	PNEC sewage treatment plant (STP)	6,58 mg/L
*	1330-20-7	xylene	PNEC sediment, freshwater	12,46 mg/kg
*	1330-20-7	xylene	PNEC sediment, marine water	12,46 mg/kg
*	1330-20-7	xylene	PNEC soil, freshwater	2,31 mg/kg

## 8.2 Exposure controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

### Personal protection equipment

#### Respiratory protection

- \* If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device Use the following filter types for cleaning waste gases:

#### Hand protection

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material:  $\geq 0,5$  mm

- \* Breakthrough time:  $\geq 1$  h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Wear anti-static footwear and clothing

### Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	transparent
Odour	characteristic
pH at 20 °C	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	56 °C
Flash point	-18 °C
flammability	not applicable
Lower explosion limit at 20°C	2,1 Vol-%
Upper explosion limit at 20°C	14,3 Vol-%
Vapour pressure at 20°C	246 mbar
Relative vapour density	not applicable
Density at 20 °C	0,889 kg/l
Water solubility at 20°C	not determined
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	460 °C

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

Decomposition temperature	not determined
Dynamic viscosity at 20 °C	2.000 mPas

**9.2 Other information**

not applicable

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2 Chemical stability**

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

**10.3 Possibility of hazardous reactions**

Gases / vapours, highly flammable. Vapours can form explosive mixtures with air.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5 Incompatible materials**

Acid, concentrated, Oxidising agent, strong.

**10.6 Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapours.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

\* **acetone; propan-2-one; propanone**

LD50: oral (Rat): = 5.800 mg/kg

LD50: dermal (Rabbit): > 15.800 mg/kg

LC50: inhalative (Rat): = 76 ppmV (4 h)

\* **ethyl acetate**

LD50: oral (Rat): > 5.620 mg/kg

LD50: dermal (Rabbit): > 18.000 mg/kg

\* **LC50: inhalative (Rat): = 56 mg/L (4 h)**

\* **xylene**

LD50: oral (Rat): = 3.523 mg/kg

LD50: dermal (Rabbit): = 12.126 mg/kg

LC50: inhalative (Rat): = 27.571 mg/m<sup>3</sup> (4 h)

**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

\* **Overall Assessment on CMR properties**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

- \* Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### 11.2 Information on other hazards

- \* **Endocrine disrupting properties**
- \* This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Based on available data, the classification criteria are not met.

##### **Acute (short-term) fish toxicity**

- \* **acetone; propan-2-one; propanone**  
LC50: (Oncorhynchus mykiss (Rainbow trout)): = 5.540 mg/L (96 h)

- \* **ethyl acetate**  
LC50: (Oncorhynchus mykiss (Rainbow trout)): = 230 mg/L (96 h)

- \* **xylene**  
LC50: (Oncorhynchus mykiss (Rainbow trout)): = 2,6 mg/L (96 h)

##### **Acute (short-term) toxicity to algae and cyanobacteria**

- \* **acetone; propan-2-one; propanone**  
ErC50: = 100 mg/L (96 h)
- \* **ethyl acetate**  
LC50: (Desmodesmus subspicatus): = 5.600 mg/L (48 h)
- \* **xylene**  
ErC50: = 2,2 mg/L (72 h)
- \* **Acute (short-term) toxicity to crustacea**
- \* **acetone; propan-2-one; propanone**  
EC50 (Daphnia pulex (water flea)): = 8.800 mg/L (48 h)
- \* **ethyl acetate**  
EC50 (Daphnia magna (Big water flea)): = 165 mg/L (48 h)
- \* **xylene**  
EC50 (Daphnia magna (Big water flea)): = 1 mg/L (48 h)

#### 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

- \* Partition coefficient: n-octanol/water = 0,68  
Partition coefficient: n-octanol/water = -0,24

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6\* Endocrine disrupting properties

No information available.

#### 12.7 Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- \* **Product/Packaging disposal**  
Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
**Waste codes/waste designations according to EWC/AVV**



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances

**Other disposal recommendations**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1 UN number or ID number**

UN 1133

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

- \* Adhesives (acetone; propan-2-one; propanone, ethyl acetate)

**Sea transport (IMDG)**

- \* Adhesives (contain acetone; propan-2-one; propanone, ethyl acetate)

**Air transport (ICAO-TI / IATA-DGR)**

- \* Adhesives (contain acetone; propan-2-one; propanone, ethyl acetate)

**14.3 Transport hazard class(es)**

Land transport (ADR/RID)	3
Sea transport (IMDG)	3
Air transport (ICAO-TI / IATA-DGR)	3

**14.4 Packing group**

Land transport (ADR/RID)	II for packages < = 450 litres: III
* Sea transport (IMDG)	II for packages < = 450 litres: III
Air transport (ICAO-TI / IATA-DGR)	II for packages < 30 litres: III

**14.5 Environmental hazards**

Land transport (ADR/RID)	not applicable
Sea transport (IMDG)	not applicable

**14.6 Special precautions for user**

- \* Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
Advices on safe handling: see parts 6 - 8

**14.7 Maritime transport in bulk according to IMO instruments**

No transport as bulk according to IBC Code.

**14.8 Additional information**

**Land transport (ADR/RID)**

tunnel restriction code: D/E for packages < = 450 litres: E

- \* Special provisions: SV 640C  
Limited quantity (LQ): 5 Liter  
Hazard identification number (Kemler No.): 33

**Sea transport (IMDG)**

- \* Segregation group: IMDG-Code segregation group not applicable  
EmS-No.: F-E, S-D  
Limited quantity (LQ): 5 Liter

**Air transport (ICAO-TI / IATA-DGR)**

- \* not applicable

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Restrictions of occupation**

- \* Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

- \* **Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

- \* VOC-value: 720 g/l  
**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**  
**Hazard categories / Named dangerous substances**
- \* P5c FLAMMABLE LIQUIDS  
Quantity 1: 5.000t; Quantity 2: 50.000t  
**National regulations**
- \* Observe in addition any national regulations!

## 15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

	REACH No.	Substance name	CAS No. EC No.
*	01-2119471330-49	acetone; propan-2-one; propanone	67-64-1 200-662-2
*	01-2119475103-46	ethyl acetate	141-78-6 205-500-4
*	01-2119488216-32	xylene	1330-20-7 215-535-7

## SECTION 16: Other information

### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
- \* EUH066 Repeated exposure may cause skin dryness or cracking.

### Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

- Flam. Liq. 2 On basis of test data.
- Eye Irrit. 2 Calculation method.
- STOT SE 3 Narcotic effects Calculation method.

### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
OEL: Occupational Exposure Limit Value  
BLV: Biological limit values  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging  
CMR: Carcinogenic, Mutagenic and Reprotoxic  
DIN: German Institute for Standardization / German industrial standard  
DNEL: Derived No-Effect Level  
EAKV: European Waste Catalogue Directive  
EC: Effective Concentration  
EC: European Community  
EN: European Standard  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG Code: International Maritime Code for Dangerous Goods  
ISO: International Organization for Standardization  
LC: Lethal Concentration  
LD: Lethal Dose  
MWC: Maximum workplace concentration  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD: Organisation for Economic Cooperation and Development

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

320  
Version 13.3

Syntic-Total - PUR adhesive  
Revision date 30-Mar-2022

Print date 27-May-2022

---

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

**Indication of changes**

\* Data changed compared with the previous version