

Safety Data Sheet

Issue Date: 15-Aug-2014

Revision Date: 05-May-2022

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Angelus Roll Call Edge Finish Black and other colors

Other means of identification

SDS # ASP-035

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Gloss Edge Finish

Details of the supplier of the safety data sheet

Supplier Address

Angelus Shoe Polish Co.
Florence Ave.
Santa Fe Springs, CA 90670
Ph: 562-941-4242

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black/dark brown liquid

Physical state Liquid

Odor Mild acetone

Classification

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Signal Word

Danger

Hazard statements

Causes serious eye irritation
May cause drowsiness or dizziness
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Use explosion-proof equipment
Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a poison center or doctor/physician if you feel unwell
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Acetone	67-64-1	>80
Carbon Black	1333-86-4	<10
1-Methoxy-2-propanol	107-98-2	<5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First Aid Measures****General Advice**

Provide this SDS to medical personnel for treatment.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Get medical attention.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. If conscious give 2 glasses of water to dilute. Get medical attention.

Most important symptoms and effects

Symptoms Causes serious eye irritation. May cause drowsiness or dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Regular foam or carbon dioxide or dry chemical.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors are heavier than air and may travel along ground to ignition sources and flash back. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO₂).

Explosion Data

Sensitivity to Static Discharge Prevent electrostatic charge build-up by using common bonding and ground techniques.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition. Ventilate area of leak or spill.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not store above 49°C/120°F.
Packaging Materials	Empty containers retain product residue and can be hazardous.
Incompatible Materials	Strong oxidizing agents. Strong acids. Strong alkalis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
1-Methoxy-2-propanol 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Any use of this product at an elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Splash proof chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	IF TLV is exceeded, use a NIOSH/MSHA approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Odor	Mild acetone
Appearance	Black/dark brown liquid		

Color	Black/dark brown	Odor Threshold	Not determined
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	56.1 °C / 133 °F		
Flash Point	-15.5 °C / 4 °F	TCC	
Evaporation Rate	14.4	(butyl acetate = 1)	
Flammability (Solid, Gas)	Not determined		
Flammability Limits in Air			
Upper Flammability Limits	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	185 mmHg	@ 68°F (20 °C)	
Vapor Density	Not determined		
Relative Density	0.89		
Water Solubility	Not determined		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		
<u>Other Information</u>			
VOC Content	100 g/L		
Density	6.7 lbs/gal @ 77°F		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from heat, sparks and open flame.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong alkalis.

Hazardous Decomposition Products

Carbon monoxide, Carbon dioxide (CO₂), Various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes serious eye irritation.
Skin Contact	May cause temporary irritation on skin contact.
Inhalation	May cause drowsiness or dizziness.
Ingestion	May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1-Methoxy-2-propanol 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h

Information on physical, chemical and toxicological effects

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	Carbon black is a possible carcinogen when it appears as a respirable dust.
------------------------	---

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

STOT - single exposure	May cause drowsiness or dizziness.
-------------------------------	------------------------------------

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	5,834.00 mg/kg
ATEmix (dermal)	10,638.00 mg/kg
ATEmix (inhalation-dust/mist)	94.90 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50
1-Methoxy-2-propanol 107-98-2		20.8: 96 h Pimephales promelas g/L LC50 static 4600 - 10000: 96 h Leuciscus idus mg/L LC50 static	23300: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Acetone 67-64-1	-0.24
1-Methoxy-2-propanol 107-98-2	-0.437

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1263
 Proper Shipping Name Paint related material
 Hazard Class 3
 Packing Group II

IATA

UN/ID No UN1263
 Proper Shipping Name Paint related material
 Hazard Class 3
 Packing Group II

IMDG

UN/ID No UN1263
 Proper Shipping Name Paint related material
 Hazard Class 3
 Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINC	ENCS	IECSC	KECL	PICCS	AICS
Acetone	X	X	X	Present	X	Present	X	X
Carbon Black	X	X	X	Present	X	Present	X	X
1-Methoxy-2-propanol	X	X	X	Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINC - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Carbon Black 1333-86-4	X	X	X
1-Methoxy-2-propanol 107-98-2	X	X	X

16. OTHER INFORMATION

NFPA**Health Hazards****Flammability****Instability****Special Hazards**

2

3

0

Not determined

HMIS**Health Hazards****Flammability****Physical hazards****Personal Protection**

2

3

0

Not determined

Issue Date: 15-Aug-2014
 Revision Date: 05-May-2022
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet